

# Analog Handheld Radio

# 5710

# PROFESSIONAL TWO-WAY RADIO

## CUSTOMER CUSTOMIZATION



## Technical Specification

General specification	
Frequency range	VHF:136-174MHz UHF:400-520MZH
Channel capacity	199(optional)
Way to work	Same Frequency Simplex or Different Frequency Simplex
Voltage	8.4V DC ± 20%
Frequency stability	± 2.5ppm
Operating Temperature	-20 ~ +50℃
Dimension(heightXwidthXdepth)	280X60X35mm
Weight	330G
Output power	2W/3W/5W
Transmitter	
Modulation	16KΦF3E
Selectivity	≥60dB
S/N	≥45dB
FM	≤-36dB
Audio response	6dB/Each octave
Audio Distortion	≤3%

Receiver	
Sensitivity	≤0.25uV
Selectivity	≥60dB
Spurious Rejection	≥80dB
Audio response	8.4V DC ± 20%
S/N	≥50dB
Audio Distortion	≤3%
Audio output level	22dBmW(10%hours)
Audio response	8.4V DC ± 20%
S/N	≥50dB
Rated Output Power	≤3%
Audio output level	22dBmW(10%hours)

Quanzhou SENHAIXUN Electronic Technology Co.,Ltd

### Product overview

Adoptign newest polymer Li-ion battery	Low power alarm	200hours super-long standby time
Output power: 5W	H/L output selective	squelch level adjust
Phrase-lock technology	Channel scan/Scanning add	TOT
W/N bandwidth	Emergency alarm function	DTCSS/DCS



**Quanzhou Senhaixun Electronic Technology Co., Ltd**  
 ADD:Huida Techonlogy Base,No.7 Zihua Road, Jiangnan Hi-Tech  
 Electronic Industrial Zone,Licheng District,Quanzhou City,Fujian,China

Quanzhou Senhaix Electronics Technology Co., Ltd. reserves the rights to change product designs and specifications without notice.All information has been seriously checked in order to be accurately. Our company does not take any responsibility if there is any consequence because of errors in printing or translation.

There may be some slight differences between product in the manual and real product during the printing process

All belongs to legitimate trademark of Quanzhou Senhaix Electronics Technology Co., Ltd.